

LTF4C402 LED Directional Lightbar



LTF4C404 LED Directional Lightbar



LTF4C406 LED Directional Lightbar



LTF4C408 LED Directional Lightbar



LTF4C412 LED Directional Lightbar



LED688-2A Directional LED Light Bar



LED688-2A-DC Directional LED Light Bar




LTF-3200DF Directional Bar




SPECIFICATION(LTF4C402/LTF4C406/LTF4C408/LTF4C412):

- Powered by 12V
- 11 feet of cable provided
- 16 available flash patterns
- Life Span of 100,000 hours
- Anti-glare coating on outer lens
- Runs on Generation 3 LED lighting
- 2 modules with 2 linear LEDs in each(LTF4C402)
- 4 modules with 4 linear LEDs in each(LTF4C404)
- 6 modules with 6 linear LEDs in each(LTF4C406)
- 8 modules with 8 linear LEDs in each(LTF4C408)
- 12 modules with 12 linear LEDs in each(LTF4C412)
- Includes control box with On/off switch
- Includes L-shaped brackets for mounting
- Flash pattern & Directional changer included

LTF4C402



LTF4C404



LTF4C406



LTF4C408



LTF4C412




LED688-2A



LED688-2A-DC



LTF-3200DF



SPECIFICATION(LED688-2A):

- Use imported LED 1W tubes and brighter, low consumption, long service time.
- 15 kinds of flash pattern.
- Colors: Red, blue, green, amber and white.
- Use special microchip controlling circuit.
- Adopting international standardized cigarette plug.
- Set indoor or outdoor by suction cup or screw.

SPECIFICATION(LED688-2A-DC):

- 8 head undercover GEN 3.5 LEDs interior split lightbar
- Uses an included visor bracket
- 24 Gen 3.5 - 1W LEDs

SPECIFICATION(LTF-3200DF):

- Weather proof housing 8 x 60-Watt halogen bulbs
- Directions: right, left, and altogether
- Mounting brackets and hardware included

LED265 Super LED Lighthouse



LTF4E404 LED Directional Lightbar



LTF4E406 LED Directional Lightbar



LTF4E408 LED Directional Lightbar



LED688-2L Lightbar



LED688-3L Lightbar



LED688-4L Directional Lightbar



LED688-6L Directional Lightbar



LED688-8L Directional Lightbar



LTF4B404 LED Directional Lightbar



LTF4B408 LED Directional Lightbar



SPECIFICATION(LED265/LTF4E404/LTF4E406/LTF4E408):

- Voltage : DC 12/24V
- Fix with 8 LED light Modules(LED265:2 LED light Modules; LTF4E404:4 LED light Modules; LTF4E406:6 LED light Modules; LTF4E408:8 LED light Modules) which installed LED261 module.
- Adopt aluminium housing and make the lights strong , also with good appearance, brightness LED light source
- Built-in installation screw on module
- It's easy to change and repair, With feature of environmental
- Protection ,energy saving and multi-function
- It's with control box to change the flash modes, 15 kinds of

LED256



LTF4E404



LTF4E406



LTF4E408



LED688-2L



LED688-3L



LED688-4L



LED688-6L



LED688-8L



LTF4B404



LTF4B408



flash modes for choice.

- It is suitable for usher, illume road, on the specially hardworking and special vehicles.

SPECIFICATION(LED688-2L/688-3L/688-4L/688-6L/688-8L):

- 12V and 12 feet of cable provided
- 15 available flash patterns and Life Span of 100,000 hours
- All of Generation 3 Linear LED technology and one module with 6 LEDs in each
- Anti-glare coating on outer lens and flashback preventing visor included
- Includes L-shaped brackets for mounting also cigarette plug or Two buttons switch box and suction mounts.

LED688-3 Lightbar



LED688-4 Lightbar



LED688-6 Directional Lightbar



LED688-7 Directional Lightbar



LED688 Directional Lightbar



LED668 Traffic Advisor



LED-3200DF LED Directional Bar



SPECIFICATION(LED688-3/LED688-4/LED688-6/LED688-7/LED688):

- 12V and 12 feet of cable provided
- 15 available flash patterns
- Life Span of 100,000 hours
- All of Generation 3 Tir LED technology
- One module with 4 LEDs in each Anti-glare coating on outer lens and flashback preventing visor included
- Includes L-shaped brackets for mounting also cigarette plug or two buttons switch box and suction mounts

SPECIFICATION(LED668):

- High intensity LED modules
- Durable, rugged construction and End warning LED modules
- 100,000 hours life span
- Light weight of six pounds
- 12-foot cord with in line fuse connects directly to the battery

LED688-3



LED688-4



LED688-6



LED688-7



LED688



LED668



LED-3200DF



- Anti-glare coating on outer lens
- 8 array LED modules with 3 flash patterns: left, right and warning-flash with 3 button control
- Cigarette light plug can be installed
- L-shaped brackets allow for hard mount
- Built-in on/off switch and direction changer
- We can make it with any size according to customer's requirement

SPECIFICATION(LED-3200DF):

- Powered by 12V 9 feet of cable provided
- 16 available flash patterns Life Span of 100,000 hours
- Anti-glare coating on outer lens
- And runs on 8 modules Generation II LED of master lights.
- Aluminum alloy shell with one controller to control the direction

LED63-2A Double Light Bar



LED63-2 Double Light Bar



LED63-4 Double Directional Light Bar



LED63-6 Double Directional Light Bar



LED69-2 Lightbar



LED69-4 Directional Lightbar



LED69-6 Directional Lightbar



LED69-8 Directional Lightbar



LED63-2A



LED63-2



LED63-4



LED63-6




LED69-2



LED69-4



LED69-6



LED69-8



SPECIFICATION(LED63-2A/LED63-2/LED63-4/LED63-6):

- Powered by 12V and 12 feet of cable provided
- 16 available flash patterns
- Life Span of 100,000 hours
- Generation 3 LED technology and
- 1 modules with 6 LEDs in each(LED63-2A)
- 2 modules with 6 LEDs in each(LED63-2)
- 4 modules with 6 LEDs in each(LED63-4)
- 6 modules with 6 LEDs in each(LED63-6)
- Anti-glare coating on outer lens
- Includes L-shaped brackets for mounting
- Dimensions:
 - LED63-6 : 57.4 cm L x 8.8cm W x59cm H
 - LED63-4 : 39.4 cm L x 8.8cm W x59cm H
 - LED63-2 :21.4 cm L x 8.8cm W x59cm H
 - LED63-2A :12.4 cm L x 8.8cm W x59cm H

SPECIFICATIO(LED69-2/LED69-4/LED69-6/LED69-8):

- Use imported LED 1W tubes and brighter, low consumption, long service time
- 15 kinds of flash pattern. Colors: Red, blue, green, amber and white
- Use special microchip controlling circuit
- Adopting international standardized cigarette plug
- Set indoor or outdoor by suction cup or screw
- Various length to choose
- Dimensions:
 - LED69-8: 920(L)x88(W)x(59-74)(H) (cm)
 - LED69-6: 690(L)x88(W)x(59-74)(H) (cm)
 - LED69-4: 460(L)x88(W)x(59-74)(H) (cm)
 - LED69-2: 230(L)x88(W)x(59-74)(H) (cm)